SIEMENS



Environmental Product Declaration

Product Type of equipment

GDBxxx.xA/xx ... GDBxxx.xX/xx

 $\mathsf{GLBxxx.xA/xx} \; ... \; \mathsf{GLBxxx.xX/xx}$

GDExxx.xA/xx ... GDExxx.xX/xx GSFxxx.xA/xx ... GSFxxx.xX/xx

2...26 kWh/a

Designation Damper Actuator

Product line OpenAir TM

Process control Siemens Switzerland Ltd.

Gubelstrasse 22 6301 Zug

 Management System
 since
 by

 ISO 14001
 (Environment)
 20.10.1998
 BSI

 ISO 9001
 (Quality)
 22.07.1986
 BSI

Product use Typical energy consumption per year

Maintenance Not necessary

Fire protection according to EN60730 & UL873

Fire load 7...9 MJ

Packaging 20-PAP Corrugated fiber board Cardboard & Paper 56 g

Notes on disposal One-way, recyclable

Risk of fire

| Materials | | | | Total weight device | 479726g |
|------------------|------------|-------------------|--------|----------------------------|----------|
| Plastics | | POM | | Various Mechanical Parts | 535 g |
| | | ABS+PC GF 10 | | Housing | 6786 g |
| | | ABS | | Cover | 45 g |
| | | PA66 GF 30 | | Various Mechanical Parts | 012 g |
| | | PA | | Various Mechanical Parts | 04 g |
| | | PUR | | Various Mechanical Parts | 12 g |
| | | PA66 RF 20 | | Various Mechanical Parts | 1113 g |
| | | PA6 GF30 | | Various Mechanical Parts | 06 g |
| | | Q Silicone rubber | | Various Mechanical Parts | 02 g |
| | | PC GF 10 | | Various Mechanical Parts | 01 g |
| Metals | | Steel | | Various Steel Parts | 191222 g |
| Others | | PVC | | PVC Cable | 70175 g |
| | | Steel / Copper | | Synchronous Motor / Magnet | 83 g |
| PCB assembled | FR4 / CEM1 | | SnAgCu | 3P Types | 6 g |
| | FR4 / CEM1 | | SnAgCu | 010V | 26 g |
| | FR4 / CEM1 | | SnAgCu | VAV MK2 | 25 g |
| | FR4 / CEM1 | | SnAgCu | VAV Comm- Version | 36 g |

Disposal

The device should not be disposed of as unsorted municipal waste. The special treatment for specific components may be mandated by law or ecologically sensible. Observe all local and applicable laws.

Comments

Materials

The device is free from substances banned by the Directive 2002/95/EC (RoHS): Pb, Hg, Cr6+, PBB, PBDE: < 0.1 % by weight in homogeneous materials

Cd: < 0.01 % by weight in homogeneous materials

SPECIAL COMPONENTS:

PVC POWER CABLE: 1.5m => +35g / 2.5m => +105g / 5m => +280g

PVC OPT. POTENTIOMETER CABLE: 1.5m => +35g / 2.5m => +105g / 5m => +280g

PVC SWITCHES CABLE: 1.5m => +50g / 2.5m => +150g / 5m => +400g

Environmental benefits

HIGH TORQUE / FORCE AT SMALL SIZE AND WEIGHT!

LOW POWER CONSUMPTION: 2...3VA

EASILY DEMOUNTABLE

Emissions

This declaration is for information purpose only.

This Environmental Product Declaration does not constitute a guarantee of the composition of a product, neither does it guarantee that the product will retain a particular composition for a particular period.

Siemens Switzerland Ltd therefore does not assume liability for any error or for any consequences which may arise from the use of this information to the maximum extent under the law.

Please contact your local Siemens branch office to get further information on environmental aspects and disposal.