


Product Environmental Profile

iC60



Schneider
Electric

Product Environmental Profile - PEP

Product overview

The main purpose of the iC60 circuit breaker is to ensure protection of low voltage electrical installations.

This range consists of circuit breakers rated 0.5A to 63A:

- Complying with IEC/EN 60898-1, IEC-60947-2
- With instantaneous tripping curves type B, C, D.
- With short circuit current breaking capacity defined by letter N, H.
- With 1P, 1P+N, 2P, 3P, 3P+N, or 4P.


The representative product used for the analysis is iC60N 1P 16A B, reference is A9F03116.

The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with the similar technology.

The extrapolation rules are described in the following chapters. The environmental analysis was performed in conformity with ISO 14040. This analysis takes the stages of the life cycle of the product into account.

Constituent materials

The mass of the product range is from 114g and 540g including packaging. It is 115g for the iC60N 1P 16A B. The constituent materials are distributed as follows:



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2002/95/EC of 27 January 2003) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric [Green Premium website](http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page) .
(<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>)

Manufacturing

The iC60 is manufactured at a Schneider Electric production site on which an ISO14001 certified environmental management system has been established.

Distribution

The weight and volume of the packaging have been optimized, based on the European Union's packaging directive. The iC60, packaging weight is 3.01g. It consists of paper (0.52g) and cardboard (2.49g).

The product distribution flows have been optimised by setting up local distribution centres close to the market areas.

Product Environmental Profile - PEP

Use

The products of iC60 circuit breaker do not generate environmental pollution (noise, emissions) requiring special precautionary measures in standard usage phase. The dissipated power depends on the conditions under which the product is implemented and used.

This dissipated power spreads out between 1.3 W and 13.8 W for the iC60 circuit breaker product range. It is 4 W for iC60N 1P 16A B

This thermal dissipation represents less than 0.06% of the power which passes through the product.

End of life

At end of life, the products in the iC60 have been optimized to decrease the amount of waste and allow recovery of the product components and materials. This product range doesn't need any special end-of-life treatment. According to countries' practices this product can enter the usual end-of-life treatment process. The recyclability potential of the products has been evaluated using the "ECO DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME). According to this method, the potential recyclability ratio is 53%. As described in the recyclability calculation method this ratio includes only metals and plastics which have proven industrial recycling processes.

Environmental impacts

Life cycle assessment has been performed on the following life cycle phases: Materials and Manufacturing (M), Distribution (D), Installation (I) Use (U), and End of life (E).

Modelling hypothesis and method:

- The calculation was performed on the iC60N 1P 16A B

- Product packaging: Is included

- Installation components: No special components included.

- Scenario for the Use phase: This product range is included in the category "Energy passing product": (assumed service life is 20 years and use scenario is: Product dissipation is 4W full load, loading rate is 30% and service uptime percentage is 30%.

- - The geographical representative area for the assessment is Europe and the electrical power model used for calculation is European model. End of life impacts are based on a worst case transport distance to the recycling plant (1000km).

Presentation of the product environmental impacts

Environmental indicators	Unit	A9F03116					
		S = M + D + I + U + E	M	D	I	U	E
Raw Material Depletion	Y-1	4.99E-14	4.97E-14	1.89E-19	0.00E+00	2.46E-16	2.33E-19
Energy Depletion	MJ	2.29E+02	1.17E+01	1.39E-01	0.00E+00	2.17E-02	1.71E-01
Water depletion	dm ³	3.68E+01	5.45E+00	1.32E-02	0.00E+00	3.13E+01	1.62E-02
Global Warming	g≈CO ₂	1.17E+04	7.79E+02	1.10E+01	0.00E+00	1.09E+04	1.35E+01
Ozone Depletion	g≈CFC-11	7.79E-04	1.68E-04	7.78E-06	0.00E+00	5.94E-04	9.55E-06
Air Toxicity	m ³	2.05E+06	2.35E+05	2.07E+03	0.00E+00	1.81E+06	2.55E+03
Photochemical Ozone Creation	g≈C ₂ H ₄	4.06E+00	3.38E-01	9.40E-03	0.00E+00	3.70E+00	1.15E-02
Air acidification	g≈H ⁺	1.62E+00	1.40E-01	1.40E-03	0.00E+00	1.48E+00	1.72E-03
Water Toxicity	dm ³	3.35E+03	2.26E+02	1.38E+00	0.00E+00	3.12E+03	1.69E+00
Water Eutrophication	g≈PO ₄	1.13E-01	8.73E-02	1.83E-04	0.00E+00	2.57E-02	2.25E-04
Hazardous waste production	kg	1.92E-01	1.03E-02	4.09E-06	0.00E+00	1.81E-01	5.02E-06

Life cycle assessment has been performed with the EIME software (Environmental Impact and Management Explorer), version 4.0, and with its database version 11.0.

The life cycle analysis shows that the U phase is the life cycle phase, which has the greatest impact on the majority of environmental indicators. Extrapolation rules for product range: Depending on the impact analysis, the environmental indicators (except RMD) of other products in this family may be proportional extrapolated by power dissipation of the product. For RMD, impact may be proportional extrapolated by mass of the product.

System approach

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Glossary

Raw Material Depletion (RMD)	This indicator quantifies the consumption of raw materials during the life cycle of the product. It is expressed as the fraction of natural resources that disappear each year, with respect to all the annual reserves of the material.
Energy Depletion (ED)	This indicator gives the quantity of energy consumed, whether it be from fossil, hydroelectric, nuclear or other sources. This indicator takes into account the energy from the material produced during combustion. It is expressed in MJ.
Water Depletion (WD)	This indicator calculates the volume of water consumed, including drinking water and water from industrial sources. It is expressed in dm ³ .
Global Warming (GW)	The global warming of the planet is the result of the increase in the greenhouse effect due to the sunlight reflected by the earth's surface being absorbed by certain gases known as "greenhouse-effect" gases. The effect is quantified in gram equivalent of CO ₂ .
Ozone Depletion (OD)	This indicator defines the contribution to the phenomenon of the disappearance of the stratospheric ozone layer due to the emission of certain specific gases. The effect is expressed in gram equivalent of CFC-11.
Air Toxicity (AT)	This indicator represents the air toxicity in a human environment. It takes into account the usually accepted concentrations for several gases in the air and the quantity of gas released over the life cycle. The indication given corresponds to the air volume needed to dilute these gases down to acceptable concentrations.
Photochemical Ozone Creation (POC)	This indicator quantifies the contribution to the "smog" phenomenon (the photochemical oxidation of certain gases which generates ozone) and is expressed in gram equivalent of ethylene (C ₂ H ₄).
Air Acidification (AA)	The acid substances present in the atmosphere are carried by rain. A high level of acidity in the rain can cause damage to forests. The contribution of acidification is calculated using the acidification potentials of the substances concerned and is expressed in mode equivalent of H ⁺ .
Water Toxicity (WT)	This indicator represents the water toxicity. It takes into account the usually accepted concentrations for several substances in water and the quantity of substances released over the life cycle. The indication given corresponds to the water volume needed to dilute these substances down to acceptable concentrations.
Hazardous Waste Production (HWP)	This indicator calculates the quantity of specially treated waste created during all the life cycle phases (manufacturing, distribution and utilization). For example, special industrial waste in the manufacturing phase, waste associated with the production of electrical power, etc. It is expressed in kg.

Date of issue:	01-2013
Period of validity:	4 years
In line with PCR	PCR-ed 2-EN-2011 12 09
Program information for PCR	www.pep-ecopassport.org
Independent verification of the declaration and data, according to compliance with ISO 14025:2006	
Internal	X
External	
Compliant with ISO 14025:2006 type III environmental declarations	
The content of this PEP cannot be compared with content based on another program.	

Schneider Electric Industries SAS

35, rue Joseph Monier
 CS 30323
 F- 92506 Reuil Malmaison Cedex
 RCS Nanterre 954 503 439
 Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric